

FLUID SEPARATION DEVICES, SYSTEMS AND/OR METHODS
USING A FLUID PRESSURE DRIVEN AND/OR BALANCED APPROACH

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This case claims the benefit of priority of U.S. Provisional patent application serial No. 60/245,282 filed on November 2, 2000.

10

INTRODUCTION

The present invention is directed generally to centrifugal fluid separation devices and is more particularly concerned with a pressure driven and/or balanced separation device preferably having a disposable, non-invasively driven, loopless rotor disposed in a rotating-sealless relationship with the entry and exit flow tubing lines.

BACKGROUND OF THE INVENTION

A number of fluid separation devices have been known and various models are currently available for the separation of blood or other composite fluids into the various component elements thereof. For example, a variety of centrifugal machines are available for separating blood into component elements such as red blood cells, platelets and plasma, *inter alia*.

25

Centrifugation for such purposes has come in many forms in both continuous and batch types. For example, in the widely used process known as continuous centrifugation, as generally opposed to batch process centrifugation, a continuous input of a composite fluid is flowed into the separation device or chamber while at the same time the components of that composite fluid are substantially continuously separated and these separated components are usually then also substantially continuously removed therefrom. Many currently popular forms of such continuous fluid separation devices include loops of entry and exit flow tubing lines connected to the

30

separation centrifuge chamber such that each loop is rotated in a relative one-omega -- two-omega ($1\omega - 2\omega$) relationship to the centrifuge chamber itself so that the tubing lines will remain free from twisting about themselves.

5 An alternative form of tubing line connection to a continuous centrifugal separation device is also available in the art which does not have such a loop, but which instead requires one or more rotating seals at the respective connections of the tubing line or lines to the centrifuge separation chamber, again to maintain the tubing lines free from twisting.

10 Batch-type centrifugation, on the other hand, usually involves separation of a composite fluid such as whole blood in a closed container, often a deformable bag, followed by a usually complicated process of automated and/or manual expression of one or more of the separated components out of the separation container or bag. A great deal of control, either automated, such as by optical interface detection, or by a diligent human operator watching a moving
15 interface, is required with such previous batch-type processes. Indeed, various means and methods have been used in prior centrifugal separation devices both continuous and batch, for driving fluid flow and for maintaining desirable interface position control between the component elements being separated thereby. For example, as mentioned, many optical control feedback methods and devices have been employed in the art. Various pumping and valving
20 arrangements are also used in various of these and other systems. Alternative, relatively automatic volume flow and density relationship interface controls have also been used. For example, in a continuous system, control outlet ports may be disposed in strategic locations relative to the separated component outlet ports.

25 Nevertheless, many facets of these prior separation devices, though satisfactorily productive, may provide certain features which are less efficient than a desired optimum. For example, centrifugal separation devices using loops of tubing lines rotated in the above-described $1\omega - 2\omega$ relationship with the centrifuge separation chamber generally require significant, usually large drive mechanisms which thereby mandate that each such entire device then also be
30 necessarily of a relatively large scale. Rotating seal devices, on the other hand, require intricate

and often operationally problematic rotating seal structures. Sterility may also be an obstacle for rotating seals. Still further, many prior drive and/or interface control systems have either been overly complex as in the case of most of the optical control models, and/or automatic volume flow/density controls may not be as desirably efficient in separation due to the usually inherent re-mixing of some quantities of the centrifugally separated components.

Hence, substantial desiderata remain to provide more highly efficient centrifugal separation devices in terms of increased efficiency fluid flow drive and separation interface controls; reduced rotor drive mechanization, quantity and/or scale; and/or reduced seal need and/or intricacy. It is toward any one or more of these or other goals as may be apparent throughout this specification that the present invention is directed.

BRIEF SUMMARY OF THE INVENTION

The present invention is directed generally to centrifugal separation devices and/or systems for use in centrifugally separating composite fluids into the component elements thereof. Such centrifugal separation devices and/or systems include unique centrifugal rotor and rotor housing combinations in which each rotor may be disposed in a freely rotatable disposition relative to the rotational device housing. Freely rotatable indicates loopless and rotating sealless as well as a preference that these rotors may be magnetically or otherwise non-invasively driven. A totally closed system may thus be provided with simple sterilization and disposability of the rotor and/or the rotor/housing combination and/or the tubing set associated therewith.

Each rotor has a substantially central fluid receiving/containing area and several fluid flow channels defined therein. In a preferred embodiment, a composite fluid to be separated into component parts may then be delivered to the fluid receiving area from which it may travel under centrifuge conditions through a fluid transport channel to a circumferential fluid separation channel where it may be subjected to substantial centrifugal forces which may separate the composite fluid into respective components. These components may then travel to distinct first

and second separated fluid outlet channels. The separated fluid components may then exit from these outlet channels and may then be moved from the separation device to a collection bag for storage or further processing or may then be returned to the donor. The composite fluid may be of various sorts, but is preferably whole blood, and the respective components may then be plasma and red blood cells (RBCs), although buffy coats and/or platelets, *inter alia*, may also be separated and harvested herewith.

The inlet channel and the first and second fluid outlet channels are preferably pre-selected to have respective inlet and first and second outlet lengths or “heights” (or relative radial distances) that are selected to be related to each other so as to provide a substantial hydraulic or hydrostatic fluid pressure balance between the outlets for the respective separated fluids flowing therethrough. Such a pressure relationship provides for forcing the fluid flow and the outlet balance preferably controls the desired location of the interface between the separated fluid components within the circumferential separation channel. The preferred outlet channel length or height relationship which provides this hydraulic balance may be derived from the general hydrostatic equation $\rho_2 g_2 h_2 = \rho_3 g_3 h_3$ wherein the length or height of the first outlet channel in this equation is h_2 , and the length or height of the second outlet channel is h_3 . These relative lengths or heights, h_2 and h_3 , may then be selected so as to provide the appropriate preferred pressure balance given a separating composite fluid to be flowed in separated fluid component parts therethrough. The other variables in the above equation are either fluid dependent, see *e.g.*, ρ_2 and ρ_3 which represent the respective densities of the separated fluids in the first and second outlet channels, or are otherwise relatively non-selectable and/or for the most part not as consequential or are relatively non-governing in the general equation, *e.g.*, the g_2 and g_3 variables are gravitational or centrifugal acceleration values preferably representing the respective average g value in each of the two columns, which may be a similar, if not a substantially equal value (*i.e.*, even though there is likely a distinction, g_2 may generally vary a relatively small amount from g_3) in normal operation. Hence, the dominant, selectable driving differences will be in the relative heights h_2 and h_3 which may simply be chosen to accommodate for any differences in the other terms, ρ or g .

Thus, for a composite fluid such as whole blood, where the respective densities of the separable component parts, *e.g.*, plasma and RBCs, are known (within sufficiently controllable ranges), then the respective heights, h_2 and h_3 may be chosen to appropriately set the location of the interface of separated components therebetween. This interface will thus remain where
5 desired, preferably in the separation channel notwithstanding a substantially continuous inflow of composite fluid to be separated and a substantially continuous outflow of separated components.

Other similarly derived relationships of interest particularly relative to the dynamic forcing of the fluid flow in this invention, *inter alia*, are also involved in the systems of the
10 present invention. For example, a further preferred aspect of the present invention involves a preferred relationship between either of the outlet fluid pressure term(s) and the inlet pressure term, particularly as these are impacted by the selection of the outlet channel heights or lengths h_2 and h_3 as described above, as well as the selection of the inlet channel height or length h_1 . Here, the fluid will flow in a continuous forward fashion so long as the inlet fluid pressure term $\rho_1 g_1 h_1$ is at least greater than either of the outlet fluid pressure terms $\rho_2 g_2 h_2$ or $\rho_3 g_3 h_3$. In an
15 equation form, this relationship is;

$$\rho_1 g_1 h_1 > \rho_2 g_2 h_2 \text{ or } \rho_3 g_3 h_3 .$$

20 This relationship governs a general forcing of the fluid flow in one direction out of the initial receiving/containment area, into the separation channel and from there, into the respective component collection areas. In the preferred embodiment where $\rho_2 g_2 h_2 = \rho_3 g_3 h_3$, then the inlet pressure term $\rho_1 g_1 h_1$ will be greater than both of the outlet pressure terms simultaneously.

25 It is to be understood that both the foregoing general description and the following detailed description are exemplary, and are intended merely to provide limited explanation of the preferred embodiments of the invention as more broadly claimed. These and further aspects of the present invention will become clearer from the detailed description read in concert with the drawings in which like component elements are referenced therein with like component numbers
30 throughout the several views.

BRIEF DESCRIPTION OF THE DRAWINGS

5 In the drawings:

Fig. 1A is an isometric schematic view of a separation device and/or system of the present invention as connected with fluid containers and a human donor;

10 Fig. 1B is an isometric schematic view of a separation device and/or system like that in Fig. 1A shown with additional alternative flow componentry;

Fig. 2 is a cross-sectional view of a centrifuge unit of a separation device like that in Figs. 1A and 1B taken along lines 2 – 2, thereof;

Fig. 3A is an isometric view of the separation layer of a centrifuge part of a separation device according to the present invention;

Fig. 3B is a plan view of the separation layer of Fig. 3A;

20 Fig. 3C is a broken-away, cross-sectional view of a portion of the separation layer of Figs. 3A and 3B, taken along line 3C—3C thereof;

25 Figs. 4A, 4B and 4C are cross-sectional views of the centrifuge unit of the separation device of Figs. 3A and 3B taken along respective lines 4A—4A, 4B—4B, and 4C—4C, thereof;

Fig. 5 is another plan view like that of Fig. 3B of a separation layer of a centrifuge unit of a separation device such as that shown in Fig. 3A;

Fig. 6 is a cross-sectional view of an alternative centrifuge unit of a separation device according to the present invention;

Figs. 7A, 7B, and 7C are cross-sectional views of still further alternative centrifuge units of alternative separation devices according to the present invention;

Fig. 8 is a plan view of an alternative separation layer of a centrifuge unit according to the present invention;

Fig. 9 is an isometric view of the alternative embodiment of the separation device of Fig. 8;

Fig. 10 is a plan view of a further alternative separation layer according to the present invention;

Fig. 11 is a plan view of a further alternative embodiment of the present invention;

Fig. 12 is an isometric view of an alternative embodiment of a separation layer like that shown in Fig. 11;

Fig. 13 is a cross-sectional view like that of Fig. 2 of an alternative embodiment of a centrifuge unit of the present invention; and

Fig. 14 is a cross-sectional view like that of Fig. 2 of an alternative embodiment of a centrifuge unit of the present invention.

DESCRIPTION OF A DETAILED EMBODIMENT

A pressure-balanced, loopless, sealless separation device according to the present invention is depicted in the attached drawings and identified by the general reference number **10** therein. Note, the processing of whole blood as the preferred composite fluid is described in the preferred embodiments herein although other composite fluids may also be processed hereby. Red blood cells (RBCs) and plasma are the primary preferred components described as separated from whole blood herein, although processing for the collection of buffy coats, platelets or white blood cells, *inter alia*, may also be accomplished herewith.

As shown for example in Fig. 1A in relation to a donor **11**, a separation device **10** may generally include a motor base **12** and a centrifuge unit **14** with a tubing system **16** having one or more tubing lines **18, 19, 20** (shown in solid lines) and associated collection or storage reservoirs or bags **22, 24**. These primary component parts and a few optional tubing lines and associated optional componentry which are shown in dashed lines in Fig. 1A and in solid and dashed lines in Fig. 1B will be further described below. Note, the option of using an anticoagulant (to be described in more detail relative to Fig. 1B) would be preferred, if not necessary in a direct donor draw like that shown in Figs. 1A and 1B. However, the composite fluid source may be other than a live donor or patient such as the donor/patient **11** shown, and could be a bag or other composite fluid container.

In the preferred embodiment, the motor base **12**, which may also be referred to as the drive portion of the separation device **10**, is preferably a table-top sized, simply transportable magnetic (or other drive-type) apparatus which in the magnetic embodiment creates a spinning magnetic field. The motor base **12** may create this spinning magnetic field by, for example, physically spinning or rotating one or more magnets disposed therein about a rotational axis defined vertically therethrough, or, the magnetic field could be created alternatively by charging one or more magnets, or electromagnetic coils, in a controlled rotational sequence as is known generally in the industry. Other alternative drive mechanisms which are preferably non-invasive, may also be used.

In any case, the centrifuge unit **14**, which may also be referred to as the centrifuge portion or part of the separation device **10**, is preferably a self-contained and disposable unit which readily mates with the motor base **12**. A preferred, readily mating relationship is as follows.

Motor base **12** is preferably a flat-topped device which generates a spinning magnetic field that emanates out of the flat-top surface **13** thereof. Centrifuge unit **14** is then a preferably flat-bottomed unit which may be readily placed or simply set upon the flat-top surface **13** of motor base **12** in operative relationship therewith. A preferably flat-bottomed surface **15** of unit **14** would thus be disposed in surface-to-surface contact with the top surface **13** of motor base **12**. In the preferred embodiments, this surface-to-surface contact relationship is preferably substantially horizontal. The axis of rotation (see description relative to Figs. 2, 3A and 3B, below) is preferably substantially perpendicular to the flat-top surface **13** of base **12** and to the flat-bottomed surface **15** of unit **14** and would thus be substantially vertical in the preferred embodiments shown and described herein.

As depicted in more detail in Fig. 2, the centrifuge unit **14** generally includes an outer housing **30** and an internal rotor assemblage **40**. In broad terms, the outer housing **30** includes a bottom wall **32** (the exterior face of which being the flat-bottom surface **15** described above), one or more circumferential walls **34**, **35**, and a top wall **36**. Bottom, circumferential, and top walls **32**, **34**, **35** and **36** are preferably contiguous (after assembly with a rotor **40**) and may at least partially be integrally conjoined or formed, although they may each be separately-formed elements which are subsequently joined. In either case, the walls preferably form a fluid-tight arrangement. A fluid inlet aperture **37a** is preferably defined in the top wall **36**, and two exit apertures **38a**, **39a** are preferably defined in, through and adjacent the lower circumferential wall **35**. Respective inlet and outlet structures **37**, **38** and **39** as shown are preferably used to define the respective apertures **37a**, **38a** and **39a**, although other forms could be used. The tubing system **16** and respective fluid storage containers **22**, **24** (not shown in Fig. 2) for example, are connected to the housing **30** as shown in Figs. 1A and 1B (and in dashed lines in Fig. 2) via the connections of tubing lines **18**, **19** and **20** with the respective aperture structures **37**, **38** and **39** (tubings **18**, **19** and **20** are the elements shown in dashed lines in Fig. 2).

Also as shown in Fig. 2, a preferred rotor **40** has three general layers; namely, a top-most layer **41** where the separation is accomplished, an intermediate layer **45** where RBCs are collected for movement to a storage container (or back to the donor **11**), and a lower layer **47** for collection of plasma. These layers will be described further below. Also note in Fig. 2 a piece of metallic material **50** is shown disposed within the lower layer **47**. At least one such piece of metallic material **50** is preferably disposed therein to interact with the rotating magnetic field generated by the base **12** to spin the rotor **40** about the rotational axis **43** (see description below) within the substantially stationary housing **30**.

The top portion or layer **41** of a preferred internal rotor **40** of centrifuge unit **14** is shown separately in more detail in Figs. 3A and 3B. In this embodiment, the top portion **41** may also be known as the separation layer of the centrifuge unit **14**. As depicted here, the top portion **41** presents a fluid flow configuration preferably providing a fluid pressure drive and balance relationship for forcing fluid flow and improving interface control. Thus, the configuration includes a substantially central fluid receiving area **42** which is connected in fluid communication with a radial transport or inlet channel **44** via a radial inlet port **44a** defined thereby. Transport channel **44** runs preferably radially outwardly to a substantially circumferential separation channel **46**. The adjective circumferential is intended here to indicate the channel which is at or near the circumference of the rotor **40**, and traverses a path which is substantially circumferential there around, yet need not be of a constant radial distance from the rotor center. Transport channel **44** is open to and fluidly communicates with the circumferential separation channel **46**. Circumferential channel **46** then runs from this intersection with the radial transport channel **44**, substantially circumferentially around the periphery of rotor **40** to the separation and outlet regions **48, 49**. Separation and outlet regions **48, 49** will be described in further detail below; however, it should first be noted that the circumferential separation channel **46** is also in fluid communication herewith, and particularly communicates with both of the two separate outlet channels **52, 54** defined here between the separation and outlet regions **48, 49**. A preferably short continuation portion **46a** of circumferential channel **46** may be defined as continuing between the first outlet channel **52** and the second outlet channel **54** and providing

fluid communication therebetween. Outlet channel **52** then connects to an outlet aperture **56** and channel **54** similarly connects to an outlet aperture **58**. These and other features are shown also in Figs. 4A-4C. For example, a cross-sectional view of the radial transport channel **44** is shown in Fig. 4A as it leads from the fluid receiving area **42** to the circumferential channel **46**. Fig. 4B shows a cross-sectional view of the first outlet channel **52** leading radially inwardly to the first outlet aperture **56**, and Fig. 4C shows a cross-sectional view of the second outlet channel **54** as it leads also radially inwardly to the second outlet aperture **58**.

As depicted primarily in Figs. 3A and 3B, as well as in the various cross-sections of Figs. 4A-4C, the respective inlet receiving area **42** and channels **44**, **46**, **52** and **54** are preferably defined by substantially vertical walls, such as the peripheral wall **62** which defines the receiving area **42**, the radial walls **64**, **65** which define the radial transport channel **44**, the respective inner and outer, substantially circumferential walls **66**, **67** defining the circumferential channel **46**, first outlet channel walls **72**, **73** defining the first outlet channel **52** and the second outlet channel walls **74**, **75** which define the second outlet channel **54**. A portion of wall **74** in the area where it is opposed to outer circumferential wall **67**, taken together with that opposed portion of wall **67**, define the preferably short continuation portion **46a** of circumferential channel **46** as located between the two outlet channels **52** and **54**. Generally, adjacent walls are preferably coterminous with each other and may thus meet at corner edges, such as the corner edge **76** disposed between adjacent walls **64** and **66** at the intersection of radial channel **44** with circumferential channel **46**. Otherwise, adjacent walls may more preferably merely blend into each other or meet in a graduated merging fashion such as that shown for the meeting of inner circumferential wall **66** with the first outlet channel wall **72** as they lead into and eventually define the first outlet channel **52**. No identifiable border need exist here between. A substantially common floor **70** may also define the bottom boundaries of the inlet area **42** and the respective channels **44**, **46**, **46a**, **52** and **54**.

An overhanging lip or ledge **60** is preferably also disposed in and around the inlet fluid receiving area **42** to retain fluids within area **42** as will be described further below. This feature is best shown in Fig. 3C, but is also depicted in Figs. 2, 3A, 3B and 4A-4C. Overhanging lips of

this sort may also be disposed on or over other walls covering other fluid passageways or channels (not shown) as may be desired. Further descriptions of such alternatives will become more apparent below. As another alternative, a covering ceiling (not shown in Figs. 1-5; but see Figs. 6 and 7A, 7B) can be attached over the respective channels and/or a substantial portion of the inlet receiving area to retain the fluids therewithin. An example of such a ceiling is shown and described with respect to the alternative embodiment of Figs. 6 and 7A, 7B which include a ceiling 80 therein, see below.

Returning now to Fig. 1A, a general description of the preferred blood and blood component flow paths, when device 10 is used for the separation of blood into components, will now be described. First, as shown here, whole blood is drawn from the donor 11 (or other source, e.g., a bag of blood) and flows through tubing line 18 to the top of the centrifuge device 14. If as shown in Fig. 1A, and as preferred, no pump is used along line 18, then tubing line 18 will be connected to the top of device 14 in a sealed but, preferably non-rotating seal fashion. Briefly, also shown in this Fig. 1A depiction, are the other tubing lines 19, 20 of tubing system 16 which display the exit flows from the centrifuge device 14 of the separated blood components; namely, red blood cells (RBCs) flowing through tubing line 19 for collection in container 22, and plasma flowing through tubing line 20 for collection in container 24. The alternative tubing line flow paths shown in dashed lines in Fig. 1A and solid and dashed lines in Fig. 1B will be discussed below. Other alternatives such as drawing the composite fluid, like blood, from a non-live donor, *i.e.* from some other fluid reservoir, will also be discussed below.

Turning to Figs. 2 - 5 (primarily Figs. 3A, 3B and 5), the flows in and through the centrifuge unit 14 of the separation device 10 will now be described. Whole blood from the donor 11 flows from the tubing line 18 down into the centrifuge unit 14 through the inlet aperture 37 defined in the top wall 36 of centrifuge unit 14 and is initially received in the fluid receiving area 42 of the separation layer 41 of the rotor 40. While in the receiving area 42, the blood is exposed to centrifugal forces when rotor 40 is spinning (which the rotor 40 is preferably doing at all times when blood is being introduced into or is otherwise resident within centrifuge unit 14). Note, the initial exposure of blood to the centrifugal forces is enhanced if the inlet

aperture 37 is eccentrically disposed relative to the axis of rotation 43 (see Figs. 2 and 3A where axis 43 is shown as a dot-dash line, and see Figs. 3B and 5 where it is shown as a crosshead indicating the perpendicularity thereof relative to the drawing sheets of Figs. 3B and 5). Under the centrifugal forces of the spinning rotor 40, the blood is moved to the periphery of the receiving area 42 and is thus generally moved into contact with the wall 62 which defines the receiving area 42. As can then be seen from Fig. 3C, the whole blood (identified generally therein by the reference number 100) is preferably held vertically within the receiving area 42 by the overhanging lip 60. The blood 100 may also take on a quasi-parabolic shape under such a lip 60 such as is shown in Fig. 3C when subjected to the centrifugal forces of a spinning rotor 40.

As shown in Figs. 3A-3C and Fig. 5, a continuous flow of the whole blood 100 will then escape from the fluid receiving area 42 into the radial channel 44. This blood will then travel radially outwardly toward and then flow into the circumferential channel 46. Flow arrows are provided in Fig. 5 to show the direction of flow throughout the preferred centrifugation configuration therein. This flow then continues on around the circumferential channel 46 for ultimate passage out of the separation layer 41 through the outlet apertures 56 and 58. First, it should be noted that when the centrifuge rotor 40 is spinning (again, as it preferably will be whenever blood is disposed therein), this will impart centrifugal forces on the blood which will then separate into at least two primary components; namely, red blood cells (RBCs) and plasma. The heavier phase RBCs will settle outwardly under these centrifugal forces, and will thus accumulate, in a still continuously circumferentially flowing fashion, against or adjacent outer wall 67 of channel 46. This action is shown in detail in Fig. 5, wherein both the radial and the circumferential flows are indicated with arrowheads in the respective channels 44, 46, 52, and 54. The RBCs are identified generally by the reference number 102 in Fig. 5, and the plasma is similarly identified generally by the reference number 104. Also, it should be noted that component separation will likely generally occur, as shown in Fig. 5, throughout the travel of the blood around the circumference of the separation layer 41 within the circumferential channel 46. For this reason, the circumferential channel 46 may also be referred to as the separation channel. Moreover, a generally counterclockwise flow pattern shown by the arrows within the channel 46 in Fig. 5 is shown however, this is not intended to be limiting as clockwise flows are also

foreseeably operable. Similarly, a clockwise rotation of the rotor 40 as indicated by the large arrow 105 in both Figs. 3B and 5 is also shown, particularly in combination with a counterclockwise flow pattern of the fluid in and through the rotor 40 (as described above), although rotation in the opposite direction is again foreseeable with or without a counterclockwise flow in rotor 40.

Even though the flow in and through the circumferential channel 46 is where a substantial part of the separation takes place such that the RBCs are forced toward the outside wall 67 (see Fig. 5), the fluid flow (as well as the fluid separation) is nevertheless preferably continuous throughout. In other words, the inlet flow of whole blood is preferably continuous as are the outlet flows of plasma and RBCs. This flow continuity is preferably driven by the relative off-set “heights” of the inlet and outlet ports 44a, 56 and 58 as will now be described in more detail. The term “heights” is used here in a fluid static, dynamic, and/or fluid pressure-balance sense for referring to various fluid distances measured from a common though generally arbitrary baseline such as the outer fluid flow separation channel circumference of the centrifuge separation layer 41 radially inwardly toward the axial center 43. However, though the inlet and/or outlet positions or “heights” are measured on a radial, each such channel need not be in a radial disposition. Circuitous flow channels not adhering to radial dispositions are available within these relationships as well. More specifically, the height of the radial transport inlet port 44a of channel 44 is the height, or represents the relative radial position of the inlet port 44a of the channel 44, also designated as h_1 in Figs. 3B and 5 from the peripheral channel wall 67 to the inlet port 44a. The outlet port heights are similarly the relative lengths or represent the relative radial outlet positions of the outlet flow channels 52, 54 and are designated h_2 and h_3 , respectively in those same Figs. 3B and 5. Then, for a fluid to be able and/or driven to flow from the inlet toward the outlets, the inlet fluid static pressure, $\rho_1 g_1 h_1$, in the transport channel 44 must be greater than either of, or in some embodiments, at least the larger of the two outlet fluid static pressures, $\rho_2 g_2 h_2$ and $\rho_3 g_3 h_3$. ($\rho_{(1, 2 \text{ or } 3)}$ is the fluid density, $g_{(1, 2 \text{ or } 3)}$ is the gravitational or centrifugal acceleration quantity and $h_{(1, 2 \text{ or } 3)}$ is the relative fluid height of each channel as described above). Thus, for the preferred positive flow in the direction of the arrows in Fig. 5;

$$\rho_1 g_1 h_1 > \rho_2 g_2 h_2 \text{ or } \rho_1 g_1 h_1 > \rho_3 g_3 h_3 \quad (\text{Equation 1}).$$

Furthermore, though accurate as a generalized concept, this summarization is both subject to simplification and/or may in other ways be somewhat over-simplified. The primary invention
5 selectable driving values are the respective **h** quantities as have been distinctly defined above. However, even though the respective **g** gravitational acceleration values are more purely non-constant variables (as depicted by the subscripts 1, 2 and 3 therein), particularly in view of the large centrifugal forces applied in the present system and the different radial lengths of each column, these may be nevertheless considered substantially similar values. Moreover, particu-
10 larly when considering the driving variable relationships herein under practical consequences (the **h**'s and **ρ**'s will vary more widely); the **g** values may be considered as substantially equivalent values throughout the above equation for each of the above pressure values (at least when operating within a substantially common centrifugal force field as well as the common gravitational field presented in a single latitude and altitude relative to the earth). In other words, the differences between the different **g** values are small enough such that the selection of the respective **h** values will accommodate them in the desired centrifugation configuration. Similarly, though the **ρ** values will likely provide greater distinctive differences for each term in this formula, the relative **h** values may be chosen to accommodate for these also. Note however, these **ρ** values are dependent on the fluids flowing herein and are not as amenable for selecting or
15 for establishing the desired configuration. In blood separation, the first **ρ** value, in $\rho_1 g_1 h_1$, is the density of the fluid in the transport channel 44; here of whole blood before separation, whereas, the second and third **ρ** values, appearing in $\rho_2 g_2 h_2$ and $\rho_3 g_3 h_3$, represent the respective densities of the fluids in the two outlet channels 52, 54; here of the separated blood components, plasma and RBCs. Moreover, the second **ρ** value, in $\rho_2 g_2 h_2$, includes both a plasma and an RBC
20 component, such that the pressure term $\rho_2 g_2 h_2$ is actually the sum of an $\rho_{RBC} g_{RBC} h_i$ value and an $\rho_{plasma} g_{plasma} (h_2 - h_i)$ value. The **h_i** value is shown in Fig. 5 as the height of the interface of the separated RBCs 102 with respect to the separated plasma 104 in or adjacent the outlet channel 52. The interface between the RBCs and plasma is identified by the general reference number 106 in Fig. 5. Thus, the hydraulic pressure term for the plasma outlet channel 52 is the
25 sum of the above interface related values as in $\rho_2 g_2 h_2 = \rho_{RBC} g_{RBC} h_i + \rho_{plasma} g_{plasma} (h_2 - h_i)$. The

terms for use in the selection of respective heights for creating the preferred positive direction flow according to Equation 1 are thus defined.

Still further, it is the location of the interface 106 between the RBCs and the plasma which is, according to the present invention, sought to be controlled such that the height, h_i , thereof remains within a certain preferred range as the interface 106 meets with wall 72 of the plasma outlet 52. This height, h_i , of interface 106 will thus preferably be so maintained by the pre-selection of the respective heights h_2 and h_3 so that they are related to each other such that the fluid pressure values of $\rho_2 g_2 h_2$ and $\rho_3 g_3 h_3$ (as generally introduced relative to Equation 1, above) are equal to each other, *i.e.*,

$$\rho_2 g_2 h_2 = \rho_3 g_3 h_3 \quad (\text{Equation 2}).$$

This then provides a hydraulic or hydrostatic pressure balance to maintain the interface at a substantially static height. But note here also, the ρ value in this $\rho_2 g_2 h_2$ has both an RBC and a plasma component such that $\rho_2 g_2 h_2$ is again the sum of a $\rho_{RBC} g_{RBC} h_i$ and a $\rho_{plasma} g_{plasma} (h_2 - h_i)$ (h_i again being the height of the interface, as shown in Fig. 5). And, Equation 2 becomes more particularly,

$$\rho_2 g_2 h_2 = \rho_{RBC} g_{RBC} h_i + \rho_{plasma} g_{plasma} (h_2 - h_i) = \rho_{RBC} g_{RBC} h_3 = \rho_3 g_3 h_3 \quad (\text{Equation 3}).$$

Moreover, the fluid pressure terms $\rho g h$ may be more accurately be considered as summations (e.g., $\Sigma(\rho g h)_n$) of contributing parts whether of unit parts of the length (e.g., where the density of a constant fluid may exhibit variation along the length or height of a column; summation or even integration may be used herewith) or when perhaps multiple fluids more accurately contribute to the pressure in a given column. As a first example, the first ρ value, in $\rho_1 g_1 h_1$, may include both a whole blood and an RBC component, such that the pressure term $\rho_1 g_1 h_1$ may actually be the sum ($\Sigma(\rho g h)_1$) of an $\rho_{RBC} g_{RBC} h_i$ value and an $\rho_{whole\ blood} g_{whole\ blood} (h_1 - h_i)$ value. The h_i value is shown in Fig. 5 as the height of the interface 106 of the separated RBCs 102 with respect to the separated plasma 104 in the peripheral channel 50. Thus, the

hydraulic pressure term for the inlet channel 44 may be the sum of the above interface related values as in

$$\rho_1 g_1 h_1 = \rho_{RBC} g_{RBC} h_i + \rho_{wholeblood} g_{wholeblood} (h_1 - h_i) \quad .$$

5

The terms for use in the selection of the respective heights for creating the preferred positive direction flow according to Equation 1 may thus be more fully defined. For example, Equation 1 can approach: $\Sigma(\rho g h)_1 > \Sigma(\rho g h)_2$, or, $\Sigma(\rho g h)_1 > \Sigma(\rho g h)_3$.

10

Similarly, the second ρ value, in $\rho_2 g_2 h_2$, includes at least a plasma and usually also an RBC component, such that the pressure term $\rho_2 g_2 h_2$ is actually the sum ($\Sigma(\rho g h)_2$) of an $\rho_{RBC} g_{RBC} h_i$ value and an $\rho_{plasma} g_{plasma} (h_2 - h_i)$ value. Thus, the hydraulic pressure term for the outlet channel 52 is the sum of the above interface related values as in

$$\rho_2 g_2 h_2 = \rho_{RBC} g_{RBC} h_i + \rho_{plasma} g_{plasma} (h_2 - h_i) \quad .$$

15

20

Note, the $\rho_3 g_3 h_3$ pressure term in these equations could also be thought of in composite parts; however, as shown and described it will generally have only one component fluid (the heavier phase separated component) and thus may be thought of more generally (for example using an average g value and an average ρ value to arrive at a single ρg value such as $\rho_{RBC} g_{RBC}$ for separated RBCs.

25

Note, in the preferred situation where $\rho_1 g_1 h_1 > \rho_2 g_2 h_2$ or $\rho_3 g_3 h_3$ and where $\rho_2 g_2 h_2 = \rho_3 g_3 h_3$, the flow dynamics here will be such that in any event where any part of any term changes, the selected relationship will bring the pressure terms as a whole back or automatically readjust to equalization. Thus, if for some reason ρ_3 were to change (e.g., become lesser or greater) during operation, then flows will change such that the interface h_i will move to counteract this change. In an example if the ρ_3 were to become greater such that the $\rho_2 g_2 h_2$ term would tend to grow in value, then the $\rho_3 g_3 h_3$ term would tend to grow, likely by flowing

faster (or likely at least not at its previous rate) and gain by raising the interface, e.g., the h_i term in the previously established relationship:

$$\rho_2 g_2 h_2 = \rho_{RBC} g_{RBC} h_i + \rho_{plasma} g_{plasma} (h_2 - h_i)$$

5

As another example, if the less dense component (e.g., plasma) lessens at any time, it will get preferential flow out of one port (e.g., the plasma port), and the heavier component (e.g., RBCs) will slow or not flow until the $\rho_2 g_2 h_2$ term increases as described above, e.g., when the h_i term rises sufficiently. Moreover, all three columns will go toward equalization in a no-flow situation (e.g., the h_i will drop to a level (particularly if no further fluid supplies the inlet channel 44) such $\rho_1 g_1 h_1 = \rho_2 g_2 h_2 = \rho_3 g_3 h_3$; at which point flow will be stopped. This provides an automatic flow stop or shutoff feature when supply of composite fluid in containment area 42 is extinguished (the heights will then generally assume a relationship such as $h_2 > h_1 > h_3$). In any event, these relationships will tend to drive toward an equalization, even if flow in one or more of the columns stops for a period; and the terms may not always be equal, but they will equalize.

10

FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100
FIG. 101
FIG. 102
FIG. 103
FIG. 104
FIG. 105
FIG. 106
FIG. 107
FIG. 108
FIG. 109
FIG. 110
FIG. 111
FIG. 112
FIG. 113
FIG. 114
FIG. 115
FIG. 116
FIG. 117
FIG. 118
FIG. 119
FIG. 120
FIG. 121
FIG. 122
FIG. 123
FIG. 124
FIG. 125
FIG. 126
FIG. 127
FIG. 128
FIG. 129
FIG. 130
FIG. 131
FIG. 132
FIG. 133
FIG. 134
FIG. 135
FIG. 136
FIG. 137
FIG. 138
FIG. 139
FIG. 140
FIG. 141
FIG. 142
FIG. 143
FIG. 144
FIG. 145
FIG. 146
FIG. 147
FIG. 148
FIG. 149
FIG. 150
FIG. 151
FIG. 152
FIG. 153
FIG. 154
FIG. 155
FIG. 156
FIG. 157
FIG. 158
FIG. 159
FIG. 160
FIG. 161
FIG. 162
FIG. 163
FIG. 164
FIG. 165
FIG. 166
FIG. 167
FIG. 168
FIG. 169
FIG. 170
FIG. 171
FIG. 172
FIG. 173
FIG. 174
FIG. 175
FIG. 176
FIG. 177
FIG. 178
FIG. 179
FIG. 180
FIG. 181
FIG. 182
FIG. 183
FIG. 184
FIG. 185
FIG. 186
FIG. 187
FIG. 188
FIG. 189
FIG. 190
FIG. 191
FIG. 192
FIG. 193
FIG. 194
FIG. 195
FIG. 196
FIG. 197
FIG. 198
FIG. 199
FIG. 200
FIG. 201
FIG. 202
FIG. 203
FIG. 204
FIG. 205
FIG. 206
FIG. 207
FIG. 208
FIG. 209
FIG. 210
FIG. 211
FIG. 212
FIG. 213
FIG. 214
FIG. 215
FIG. 216
FIG. 217
FIG. 218
FIG. 219
FIG. 220
FIG. 221
FIG. 222
FIG. 223
FIG. 224
FIG. 225
FIG. 226
FIG. 227
FIG. 228
FIG. 229
FIG. 230
FIG. 231
FIG. 232
FIG. 233
FIG. 234
FIG. 235
FIG. 236
FIG. 237
FIG. 238
FIG. 239
FIG. 240
FIG. 241
FIG. 242
FIG. 243
FIG. 244
FIG. 245
FIG. 246
FIG. 247
FIG. 248
FIG. 249
FIG. 250
FIG. 251
FIG. 252
FIG. 253
FIG. 254
FIG. 255
FIG. 256
FIG. 257
FIG. 258
FIG. 259
FIG. 260
FIG. 261
FIG. 262
FIG. 263
FIG. 264
FIG. 265
FIG. 266
FIG. 267
FIG. 268
FIG. 269
FIG. 270
FIG. 271
FIG. 272
FIG. 273
FIG. 274
FIG. 275
FIG. 276
FIG. 277
FIG. 278
FIG. 279
FIG. 280
FIG. 281
FIG. 282
FIG. 283
FIG. 284
FIG. 285
FIG. 286
FIG. 287
FIG. 288
FIG. 289
FIG. 290
FIG. 291
FIG. 292
FIG. 293
FIG. 294
FIG. 295
FIG. 296
FIG. 297
FIG. 298
FIG. 299
FIG. 300
FIG. 301
FIG. 302
FIG. 303
FIG. 304
FIG. 305
FIG. 306
FIG. 307
FIG. 308
FIG. 309
FIG. 310
FIG. 311
FIG. 312
FIG. 313
FIG. 314
FIG. 315
FIG. 316
FIG. 317
FIG. 318
FIG. 319
FIG. 320
FIG. 321
FIG. 322
FIG. 323
FIG. 324
FIG. 325
FIG. 326
FIG. 327
FIG. 328
FIG. 329
FIG. 330
FIG. 331
FIG. 332
FIG. 333
FIG. 334
FIG. 335
FIG. 336
FIG. 337
FIG. 338
FIG. 339
FIG. 340
FIG. 341
FIG. 342
FIG. 343
FIG. 344
FIG. 345
FIG. 346
FIG. 347
FIG. 348
FIG. 349
FIG. 350
FIG. 351
FIG. 352
FIG. 353
FIG. 354
FIG. 355
FIG. 356
FIG. 357
FIG. 358
FIG. 359
FIG. 360
FIG. 361
FIG. 362
FIG. 363
FIG. 364
FIG. 365
FIG. 366
FIG. 367
FIG. 368
FIG. 369
FIG. 370
FIG. 371
FIG. 372
FIG. 373
FIG. 374
FIG. 375
FIG. 376
FIG. 377
FIG. 378
FIG. 379
FIG. 380
FIG. 381
FIG. 382
FIG. 383
FIG. 384
FIG. 385
FIG. 386
FIG. 387
FIG. 388
FIG. 389
FIG. 390
FIG. 391
FIG. 392
FIG. 393
FIG. 394
FIG. 395
FIG. 396
FIG. 397
FIG. 398
FIG. 399
FIG. 400
FIG. 401
FIG. 402
FIG. 403
FIG. 404
FIG. 405
FIG. 406
FIG. 407
FIG. 408
FIG. 409
FIG. 410
FIG. 411
FIG. 412
FIG. 413
FIG. 414
FIG. 415
FIG. 416
FIG. 417
FIG. 418
FIG. 419
FIG. 420
FIG. 421
FIG. 422
FIG. 423
FIG. 424
FIG. 425
FIG. 426
FIG. 427
FIG. 428
FIG. 429
FIG. 430
FIG. 431
FIG. 432
FIG. 433
FIG. 434
FIG. 435
FIG. 436
FIG. 437
FIG. 438
FIG. 439
FIG. 440
FIG. 441
FIG. 442
FIG. 443
FIG. 444
FIG. 445
FIG. 446
FIG. 447
FIG. 448
FIG. 449
FIG. 450
FIG. 451
FIG. 452
FIG. 453
FIG. 454
FIG. 455
FIG. 456
FIG. 457
FIG. 458
FIG. 459
FIG. 460
FIG. 461
FIG. 462
FIG. 463
FIG. 464
FIG. 465
FIG. 466
FIG. 467
FIG. 468
FIG. 469
FIG. 470
FIG. 471
FIG. 472
FIG. 473
FIG. 474
FIG. 475
FIG. 476
FIG. 477
FIG. 478
FIG. 479
FIG. 480
FIG. 481
FIG. 482
FIG. 483
FIG. 484
FIG. 485
FIG. 486
FIG. 487
FIG. 488
FIG. 489
FIG. 490
FIG. 491
FIG. 492
FIG. 493
FIG. 494
FIG. 495
FIG. 496
FIG. 497
FIG. 498
FIG. 499
FIG. 500
FIG. 501
FIG. 502
FIG. 503
FIG. 504
FIG. 505
FIG. 506
FIG. 507
FIG. 508
FIG. 509
FIG. 510
FIG. 511
FIG. 512
FIG. 513
FIG. 514
FIG. 515
FIG. 516
FIG. 517
FIG. 518
FIG. 519
FIG. 520
FIG. 521
FIG. 522
FIG. 523
FIG. 524
FIG. 525
FIG. 526
FIG. 527
FIG. 528
FIG. 529
FIG. 530
FIG. 531
FIG. 532
FIG. 533
FIG. 534
FIG. 535
FIG. 536
FIG. 537
FIG. 538
FIG. 539
FIG. 540
FIG. 541
FIG. 542
FIG. 543
FIG. 544
FIG. 545
FIG. 546
FIG. 547
FIG. 548
FIG. 549
FIG. 550
FIG. 551
FIG. 552
FIG. 553
FIG. 554
FIG. 555
FIG. 556
FIG. 557
FIG. 558
FIG. 559
FIG. 560
FIG. 561
FIG. 562
FIG. 563
FIG. 564
FIG. 565
FIG. 566
FIG. 567
FIG. 568
FIG. 569
FIG. 570
FIG. 571
FIG. 572
FIG. 573
FIG. 574
FIG. 575
FIG. 576
FIG. 577
FIG. 578
FIG. 579
FIG. 580
FIG. 581
FIG. 582
FIG. 583
FIG. 584
FIG. 585
FIG. 586
FIG. 587
FIG. 588
FIG. 589
FIG. 590
FIG. 591
FIG. 592
FIG. 593
FIG. 594
FIG. 595
FIG. 596
FIG. 597
FIG. 598
FIG. 599
FIG. 600
FIG. 601
FIG. 602
FIG. 603
FIG. 604
FIG. 605
FIG. 606
FIG. 607
FIG. 608
FIG. 609
FIG. 610
FIG. 611
FIG. 612
FIG. 613
FIG. 614
FIG. 615
FIG. 616
FIG. 617
FIG. 618
FIG. 619
FIG. 620
FIG. 621
FIG. 622
FIG. 623
FIG. 624
FIG. 625
FIG. 626
FIG. 627
FIG. 628
FIG. 629
FIG. 630
FIG. 631
FIG. 632
FIG. 633
FIG. 634
FIG. 635
FIG. 636
FIG. 637
FIG. 638
FIG. 639
FIG. 640
FIG. 641
FIG. 642
FIG. 643
FIG. 644
FIG. 645
FIG. 646
FIG. 647
FIG. 648
FIG. 649
FIG. 650
FIG. 651
FIG. 652
FIG. 653
FIG. 654
FIG. 655
FIG. 656
FIG. 657
FIG. 658
FIG. 659
FIG. 660
FIG. 661
FIG. 662
FIG. 663
FIG. 664
FIG. 665
FIG. 666
FIG. 667
FIG. 668
FIG. 669
FIG. 670
FIG. 671
FIG. 672
FIG. 673
FIG. 674
FIG. 675
FIG. 676
FIG. 677
FIG. 678
FIG. 679
FIG. 680
FIG. 681
FIG. 682
FIG. 683
FIG. 684
FIG. 685
FIG. 686
FIG. 687
FIG. 688
FIG. 689
FIG. 690
FIG. 691
FIG. 692
FIG. 693
FIG. 694
FIG. 695
FIG. 696
FIG. 697
FIG. 698
FIG. 699
FIG. 700
FIG. 701
FIG. 702
FIG. 703
FIG. 704
FIG. 705
FIG. 706
FIG. 707
FIG. 708
FIG. 709
FIG. 710
FIG. 711
FIG. 712
FIG. 713
FIG. 714
FIG. 715
FIG. 716
FIG. 717
FIG. 718
FIG. 719
FIG. 720
FIG. 721
FIG. 722
FIG. 723
FIG. 724
FIG. 725
FIG. 726
FIG. 727
FIG. 728
FIG. 729
FIG. 730
FIG. 731
FIG. 732
FIG. 733
FIG. 734
FIG. 735
FIG. 736
FIG. 737
FIG. 738
FIG. 739
FIG. 740
FIG. 741
FIG. 742
FIG. 743
FIG. 744
FIG. 745
FIG. 746
FIG. 747
FIG. 748
FIG. 749
FIG. 750
FIG. 751
FIG. 752
FIG. 753
FIG. 754
FIG. 755
FIG. 756
FIG. 757
FIG. 758
FIG. 759
FIG. 760
FIG. 761
FIG. 762
FIG. 763
FIG. 764
FIG. 765
FIG. 766
FIG. 767
FIG. 768
FIG. 769
FIG. 770
FIG. 771
FIG. 772
FIG. 773
FIG. 774
FIG. 775
FIG. 776
FIG. 777
FIG. 778
FIG. 779
FIG. 780
FIG. 781
FIG. 782
FIG. 783
FIG. 784
FIG. 785
FIG. 786
FIG. 787
FIG. 788
FIG. 789
FIG. 790
FIG. 791
FIG. 792
FIG. 793
FIG. 794
FIG. 795
FIG. 796
FIG. 797
FIG. 798
FIG. 799
FIG. 800
FIG. 801
FIG. 802
FIG. 803
FIG. 804
FIG. 805
FIG. 806
FIG. 807
FIG. 808
FIG. 809
FIG. 810
FIG. 811
FIG. 812
FIG. 813
FIG. 814
FIG. 815
FIG. 816
FIG. 817
FIG. 818
FIG. 819
FIG. 820
FIG. 821
FIG. 822
FIG. 823
FIG. 824
FIG. 825
FIG. 826
FIG. 827
FIG. 828
FIG. 829
FIG. 830
FIG. 831
FIG. 832
FIG. 833
FIG. 834
FIG. 835
FIG. 836
FIG. 837
FIG. 838
FIG. 839
FIG. 840
FIG. 841
FIG. 842
FIG. 843
FIG. 844
FIG. 845
FIG. 846
FIG. 847
FIG. 848
FIG. 849
FIG. 850
FIG. 851
FIG. 852
FIG. 853
FIG. 854
FIG. 855
FIG. 856
FIG. 857
FIG. 858
FIG. 859
FIG. 860
FIG. 861
FIG. 862
FIG. 863
FIG. 864
FIG. 865
FIG. 866
FIG. 867
FIG. 868
FIG. 869
FIG. 870
FIG. 871
FIG. 872
FIG. 873
FIG. 874
FIG. 875
FIG. 876
FIG. 877
FIG. 878
FIG. 879
FIG. 880
FIG. 881
FIG. 882
FIG. 883
FIG. 884
FIG. 885
FIG. 886
FIG. 887
FIG. 888
FIG. 889
FIG. 890
FIG. 891
FIG. 892
FIG. 893
FIG. 894
FIG. 895
FIG. 896
FIG. 897
FIG. 898
FIG. 899
FIG. 900
FIG. 901
FIG. 902
FIG. 903
FIG. 904
FIG. 905
FIG. 906
FIG. 907
FIG. 908
FIG. 909
FIG. 910
FIG. 911
FIG. 912
FIG. 913
FIG. 914
FIG. 915
FIG. 916
FIG. 917
FIG. 918
FIG. 919
FIG. 920
FIG. 921
FIG. 922
FIG. 923
FIG. 924
FIG. 925
FIG. 926
FIG. 927
FIG. 928
FIG. 929
FIG. 930
FIG. 931
FIG. 932
FIG. 933
FIG. 934
FIG. 935
FIG. 936
FIG. 937
FIG. 938
FIG. 939
FIG. 940
FIG. 941
FIG. 942
FIG. 943
FIG. 944
FIG. 945
FIG. 946
FIG. 947
FIG. 948
FIG. 949
FIG. 950
FIG. 951
FIG. 952
FIG. 953
FIG. 954
FIG. 955
FIG. 956
FIG. 957
FIG. 958
FIG. 959
FIG. 960
FIG. 961
FIG. 962
FIG. 963
FIG. 964
FIG. 965
FIG. 966
FIG. 967
FIG. 968
FIG. 969
FIG. 970
FIG. 971
FIG. 972
FIG. 973
FIG. 974
FIG. 975
FIG. 976
FIG. 977
FIG. 978
FIG. 979
FIG. 980
FIG. 981
FIG. 982
FIG. 983
FIG. 984
FIG. 985
FIG. 986
FIG. 987
FIG. 988
FIG. 989
FIG. 990
FIG. 991
FIG. 992
FIG. 993
FIG. 994
FIG. 995
FIG. 996
FIG. 997
FIG. 998
FIG. 999
FIG. 1000

20

In all of these cases then, the configuration selectable values are preferably the h values. The particular fluids to be and consequently separated dictate the ρ values, and the g values are governed mainly by the centrifugal forces applied to the system. Thus, when deciding the size and relative configuration of the desired centrifugation system, the selectable values are the inlet channel length h_1 relative to outlet channel lengths h_2 and h_3 ; as well as the relative outlet lengths h_2 and h_3 to each other according to the above Equations 1, 2 and 3.

25

Control over interface 106 using Equations 2 and 3 provides a distinct advantage. First, if interface 106 were not so controlled, it could fall either radially outwardly below the extent of wall 73 such that separated plasma would spill into the RBC outlet channel 54 and undesirably dilute the RBC product flowing out outlet 58. Or, the interface 106 could alternatively, ride too high, radially inwardly, along wall 73 such that a buffy coat component and/or RBCs could spill into the plasma outlet 56. The “buffy coat” blood component, as known in the art, generally

30

rides on the interface **106**. The buffy coat generally includes platelets and white blood cells therein. And, if the interface **106** is not controlled or maintained a sufficient distance from either of the outlets **56, 58**, then these buffy coat blood components could spill into and contaminate either of the RBC or plasma products. White blood cells (WBCs) are particularly unwanted in both RBC and plasma products due to the possible contamination of such white blood cells with certain undesirable pathogens, including HIV viral contamination, for example. However, because centrifugal separation will less effectively separate WBCs from RBCs, the WBCs are more likely to be addressed separately relative to the RBCs with a post-centrifugal filtration. In other words, the present invention, like other centrifugal separation systems, will most likely not sufficiently leukoreduce red blood cells. Rather, although the buffy coat including the WBCs will preferably ride on the RBC layer, they will not likely be sufficiently separated from the RBCs here so as to produce a leukoreduced RBC product. However, the buffy coat including WBCs can be sufficiently centrifugally separated from the plasma product by the present invention so long as the height of the interface **h_i** is sufficiently controlled as taught herein.

Nonetheless, once the whole blood **100** has traveled through the separation channel **46** and has been separated into components, particularly into RBCs **102** and plasma **104**, then these components **102** and **104** will flow out through their respective outlets, namely outlets **58** and **56**. Again, as this is a continuous flow process, the whole blood **100** continuously flows into the centrifugal configuration, particularly the separation portion **41** of centrifuge unit **14**, and blood components **102** and **104** are continuously separated therein and continuously flow out of the centrifugal configuration separation portion **41** of centrifuge unit **14** through the outlets **58** and **56**. Then, for the further description of the flow process from these outlets forward, reference is turned again to Figs. 4B and 4C which show one preferred embodiment providing for the collection of the separated blood components from the separation layer outlets **58**, **56** and moving or otherwise allowing for the movement of these components out of the centrifuge unit **14** and separation device **10**.

Specifically, Fig. 4B shows an embodiment wherein the plasma outlet **56** leads to an exit passageway **57**, which, in this embodiment, first extends substantially vertically downwardly

through the rotor 40 until it reaches the lower layer 47, and then it extends radially outwardly to and through the exterior surface of the lower layer 47 of the rotor 40. This substantially L-shaped passageway 57 thus provides fluid communication from the outlet 56 to the lower interior circumferential channel 31 of the housing 30. In this way then, fluid passing through outlet 56 then flows through passageway 57 and then empties from the rotor 40 into the rotor housing 30 within the lower channel 31 thereof. Lower channel 31 is then also in fluid flow communication with the outlet 38 which thereby allows for fluid flow out of housing channel 31 into and through outlet 38, and from there, into and through tubing line 20 ultimately up to fluid container 24 (see Fig. 1A). Note, in the embodiment shown here, the fluid preferably retains an amount of kinetic energy imparted thereto by the spinning centrifuge, and this kinetic energy may be effectively converted into a fluid flow pressure which can force a non-centrifugal flow of the fluid in and through the tubing line 20, and a further flow even upwards, against the pull of gravity, into a hanging storage bag 24. The components involved in causing this action; particularly the lower layer 47 of the rotor 40, and the channel 31 of the housing 30, may thus be referred to as a pump of a centrifugal or vortex type. Note, bag 24 need not be hung above separation device 10, but may be hung on a level with or even below device 10. The quantity of kinetic energy thus required (if any) to be maintained can thus be a function of such receptacle location as well as the length of travel thereto, *inter alia*.

Similarly, as shown in Fig. 4C, the RBC outlet 58 leads to an exit passageway 59, which in the embodiment shown here, first extends downwardly through the rotor 40 until it reaches the intermediate rotor layer 45, and then it extends radially outwardly to and through the exterior surface of the rotor layer 45. Thus, as above, this RBC passageway 59 provides fluid communication from the RBC outlet 58 to an intermediate interior circumferential channel 33 of the housing 30. Fluid then passing through outlet 58 flows through passageway 59 and then empties from the rotor 40 into the intermediate channel 33 within the rotor housing 30. Channel 33 is then also in fluid flow communication with the RBC outlet 39 thus allowing for fluid flow out of channel 33 into and through outlet 39, and from there, into and through tubing line 19 ultimately up to fluid container 22 (again, see Fig. 1A). Moreover, as was true above, the fluid reaching the interior channel 33 preferably retains an amount of kinetic energy imparted thereto by the

spinning centrifuge, and this kinetic energy may here also be effectively converted into a fluid flow pressure which can cause or force a non-centrifugal flow of the fluid in and through the tubing line 19, and even up, against the pull of gravity, into a hanging storage bag 22. The components here too involved in causing this type of action; particularly the intermediate layer 45 of the rotor 40, and the channel 33 of the housing 30, may thus also be referred to as a centrifugal or vortex type of pump. Here also, bag 22 need not be above device 10 but could be on a level with or even disposed therebelow. The amount of kinetic energy thus required (again, if any) can thus be dependent on such receptacle disposition and the relative distance therefrom, *inter alia*.

Several important advantages are achieved with a device such as that shown and described herein. A first such advantage is the elimination of numerous control elements which were often required in previous centrifugal separation systems. For example, the hydraulic pressure-balanced interface controls shown and described here eliminate the need for optical or other feedback loop interface control elements. The present pressure-balance controls are also substantially independent of the blood hematocrit and relative flow rates of the inlet and outlet fluids. This eliminates the need for complex flow rate calculations and pump controls therefor (*i.e.*, eliminates computer calculations and multiple flow control pumps; in various conventional embodiments, multiple pumps, inlet and outlet, have been required to be maintained in dynamic control relationship with each other constantly by computer in order to provide proper interface control). Thus, at the least, no inflow pump is required here, and blood may instead be gravity drained/fed into this separation device. The lack of an inflow pump and use of a magnetic or an otherwise non-contact drive mechanism further eliminates the need for a rotating tubing loop. This serves to greatly reduce the quantities and sizes of the mechanical components (tubing loops in rotating loop systems generally dictate the minimum mechanical element requirements and size), and thus also allows for an overall reduction in scale of the separation device as a whole. A gravity feed system (no inflow pump) also eliminates any need for a rotating seal at the inlet connection of the inflow line to the separation device. This greatly reduces complexity and a large potential for operational failure. Also, the rotor and housing combination are easily made in a totally closed system which can be simply sterilized and can be completely disposable,

particularly if non-invasively driven by a rotational magnetic motor as described herein. The reduced scale and mechanical complexity contribute to the disposability benefits as well.

A further advantage can be realized in the output product quality. In particular, a virtually constant maximum hematocrit may be obtained for all resultant red blood cell products because the presently described separation device may be operated within a range of revolutions per minute (RPMs) at which the product hematocrit does not substantially vary. For example, the present invention may be operated at high speeds of a few to many thousands of RPMs, speeds which are heretofore not achievable for various reasons (*e.g.*, drive mechanism or rotating seal problems at such high speeds). And, at such speeds, virtually all RBCs will be separated out from the input whole blood, thus yielding an RBC product with the highest available hematocrit. Note, the highest available hematocrit is a number above 80 % and less than 100 % and which approaches a substantially constant asymptote which is in the area of approximately 90 or 95 %. At speeds in the range of high RPMs, the resulting hematocrit is virtually equivalent to the asymptotic maximum throughout that range. At much lower speeds (*e.g.*, below 3000 RPMs), the resulting hematocrit may significantly diverge from the asymptotic maximum.

Referring once again to Figs. 1A and 1B, a few basic alternatives will now be addressed. First, the use of an anticoagulant (AC) may be preferred and particularly is preferred when a direct connection to a donor 11 is made as shown in Figs. 1A and 1B. Note, the present invention may be used in a process (not shown) to separate previously collected composite fluids, like blood, without the need for anticoagulant addition (in the case of previously collected blood; such blood will very likely already have an anticoagulant added thereto, and thus does not require additional quantities thereof). Thus, an anticoagulant container 110 is shown in dashed lines in Fig. 1A, and in solid lines in Fig. 1B, as it might be incorporated into the overall system. In particular, the anticoagulant container 110 may be connected to a tubing line 112 which is in turn connected to a manifold 115 disposed in fluid communication with the blood inlet line 18 (all shown in solid lines in Fig. 1B). Such a manifold connection is known and used frequently in this field of art. The anticoagulant may then be allowed to freeflow into the tubing line 18, such freeflow being controlled by careful selection of the inside diameter of the AC tubing line 112, or

additionally and more preferably, an anticoagulant pump **140** (dashed lines in Fig. 1B) may be used to control the inflow of AC into the inlet line **18**. Peristaltic pumps for this purpose are well known in this field (as are other pump types; *e.g.*, linear piston plunger pumps, *inter alia*). A scale **136** is depicted in Figs. 1A and 1B to demonstrate one version among a plurality of known alternatives which may be used to ensure accurate AC feeding into the system.

Another basic alternative available with this invention involves the optional return of certain separated blood components back to the donor, rather than retaining these in the collection reservoirs **22**, **24**. An example embodiment for returning a quantity of either (or both) separated RBCs and/or separated plasma back to the donor **11** is also shown in Fig. 1A in dashed lines and in solid lines in Fig. 1B. In particular, three return tubing lines are shown such that a first such tubing line **120** is connected to an outlet port in RBC bag **22**, a second tubing line **122** is similarly connected to an outlet in plasma bag **24**, and a third tubing line **124** connects both of return lines **120** and **122** with the manifold **115** described above. A Y-shaped connector **125** may be used to connect lines **120**, **122** with line **124**. Then, if and/or when during a separation procedure it may be desired to return a quantity of a separated component (RBCs or plasma) to the donor **11**, the desired component may then be allowed to flow out of its respective container **22** or **24**, through its respective return line **120** or **122**, through the Y connector **125**, through the common return line **124**, into and through manifold **115**, then back toward and into the donor **11** through the donor line **18a**.

Accomplishment of these particular flows may simply involve gravity drainage of the desired blood component from its collection/storage bag **22** or **24**, and/or it may involve the use of one or more pumps, preferably of the peristaltic type, for example, see pump **142**, respective to line **124** in Fig. 1B (dashed lines). Thus, respective pumps may be engaged with each return line **120**, **122** (not shown) and/or with line **124** (pump **142**), and then may be activated at a desired operational point to pump the desired separated blood component out of its reservoir and through the respective tubings, and back into the donor **11**. Various clamps or other flow stoppage mechanisms (not shown) may also be used and variously engaged with any one or more of these tubing lines depending upon which fluid component is to be returned or not, as the case

may be. For example, if RBCs are to be returned, then a clamp or other flow stopping mechanism may be engaged with the plasma return line 122, as well, for example, as engaging if desired such a flow stopping mechanism on the main tubing line 18 (and on the AC line 112 if such is being used). Then an RBC flow may be established through the RBC return line 120
5 back to the donor 11. Note, the use of the bags 22, 24 might provide for an air or bubble trapping effect (as is known in the art) prior to return to the donor/patient 11.

Other variations abound. For example, lines 120 and 122 may each reach to the manifold 115, thus eliminating the intermediate return line 124 and Y connector 125. Also, these
10 return lines (with or without an intermediate line 124) may be run to a second needle (not shown) to alleviate concern for altering (e.g., stopping or clamping) flow through main line 18 for periods or modes of blood return. Another example may include the use of an intermediate reservoir (not shown), for example, at the connection of the return lines 120, 122 to the
15 intermediate line 124 (e.g. at the location depicted by, and in lieu of, the Y-connection mechanism 125). Such a reservoir could fulfill several goals, as for example, providing an air or bubble trap (as is known in the art) prior to return of components to the donor/patient 11. This may be a redundancy to bags 22, 24 or could remove air perhaps introduced by such bags 22, 24, or such an intermediate reservoir could provide a sort of holding capacity in a single needle system such that separated components may be accumulated therein until a certain amount is
20 achieved at which point an automatic (or manual) control mechanism could switch on a pump 142 to activate a return cycle for return of the accumulated components to the donor/patient 11. As above, such a switch could also entail a clamping of the inlet flow line 18, or perhaps this inlet flow may remain undisturbed during such a return cycle.

25 Such an intermediate reservoir might also be useful with a further alternative embodiment shown in dashed lines in Fig. 1B; the use of optional direct tubing connections from the separated component outlets to the donor return lines. See in particular branch connection lines 121 and 123 in Fig. 1B (dashed lines). Note, these connection lines may merely flow back to the donor without being connected to an outlet line from the respective reservoirs. A flow or
30 flows of separated components can thus be diverted back to the donor 11 prior to being

accumulated in either respective collection storage bag **22, 24**. Such directed flow(s) could then run through the respective return line **120** and/or **122**, into and through Y-connector **125** and back to the donor **11**. Or, these diverted flows could be captured by the above-described intermediate reservoir (not shown) and accumulated prior to return as described. Further optional features which could be used herewith include the switch valves **150, 152** (shown in dashed lines in Fig. 1B) on the separated component outlet lines **19, 20** and/or coactive also with the branch connecting **121, 123**. Switch valve mechanisms **150, 152** can be used to divert flow from the main outlet lines **19, 20** directly back to the donor/patient **11**. For example, the switch valve **150** can be used either to close off a branch line connection **121** so that flow continues from line **19** into bag **22** or to close off flow through the upper part **19a** of RBC outlet line **19** and thereby divert flow through branch line **121**. Flow through branch line **121** then connects to return line **120** and from there goes back to the donor/patient **11** through connector **125**, line **124** and manifold **115**. As above, an intermediate reservoir could catch such a re-directed flow and trap bubbles therefrom and/or hold it until a return cycle is called for. Otherwise, particularly in a two needle set-up, the flow may be substantially continuously directed back to the donor/patient **11**. A similar action may be created by the switch valve **152** which may close off a branch line **123** to maintain flow from line **20** to bag **24**, or switch valve **152** may be directed to close off the upper part **20a** of line **20** and thereby open up flow to and through branch connection line **123**. Flow through line **123** may then connect with return line **122** and flow from there goes back to the donor/patient **11** through the Y-connector **125** (or the unshown intermediate reservoir), line **124** and manifold **115** to the donor/patient part **18a** of line **18** for return of the components to donor/patient **11**. Lines **120** and/or **122** may then be preferably disposed clamped closed (not shown) above the branch connections **121** and/or **123** or may simply be not connected to the outlets of bags **22** and/or **24** contrary to the alternative which is shown in Fig. 1B.

Another consideration is that these manipulations, *i.e.*, clamping certain lines and/or initiating certain flows whether by pump or otherwise, may be performed manually by a human operator (albeit with certain instructions and/or following certain hierarchical processes), or may be performed by a control device (not shown), which may interpret certain input and/or sensed

conditions and perform the appropriate flow control actions therefor or in response thereto. Thus, if for example, a preferred quantity of a separated component (RBCs or plasma) is collected within a storage receptacle, but the other component has not yet reached its desired yield, then the control device may then divert the continuously accumulating excess back to the donor 11, while and until the other component reaches its target yield so that both components may have been collected to preferred yields. This the control device may accomplish by operation of machine-activated clamps and/or peristaltic pumps at the appropriate points. Scales 132, 134, or other quantity measuring devices (not shown) may optionally be used to determine the quantities of separated components collected in the respective bags 22, 24. The scale derived quantities may then be used by either the human operator or the optional control device to determine which steps for continued collection or return may be desired. An optional scale 136 (as introduced above) or other quantity measuring device may also be used in the optional AC administering system, such that it may, for example, provide feedback to a control device so that the control device may determine how much AC will be/has been delivered and thus whether and to what extent corrective flow measures (*e.g.*, more or less pumping) may be necessary or desired.

Note, as shown and described for the most part throughout this specification, the inlet to centrifugal separation device 10 and the outlets from device 10 have preferably not required external pumping means (the inlet through tubing line 18 is preferably gravity driven; and the outlet flows through tubing lines 19 and 20 preferably were driven by centrifugal energy retained in the fluid as it exited the centrifuge separation layer 41 and/or may also be gravity driven). However, other motive means may be employed for any/either of these flows as well. For a first example, a peristaltic or other fluid pump 144 (dashed lines in Fig. 1B) may be used to draw blood from the donor/patient 11 and feed the blood to the separation device 10. However, it should be noted that such an assist, if providing much of an increase over a gravitational pull, will likely require the additional employment of an inlet seal which is not shown in the drawings. An example of such a seal could be a rotating seal, or it could take other forms and thereby require further mechanical inlet flow control means such as a 1T - 2T loop (described herein-above); and though viable these alternatives are thus less desirable. Even so, the geometries of

the centrifugal configuration as shown in the separation layer **41** and described hereinabove, may still provide attractive advantages even in such more complicated alternatives.

Similarly, though centrifugal forces are preferred for moving the separated components out of device **10**, other motive means may be used here as well. As a first example (not shown but introduced above), the collection bags **22**, **24** may be disposed lower than the separation device **10** and the separated components may then be gravity-drained thereto from device **10**. The left-over kinetic energy from the centrifugal process may or may not be used in an adjunct hereto. Another alternative involves the use of external pumps **146**, **148** (dashed lines, Fig. 1B) of preferably peristaltic or other alternative types to move the separated components from device **10** through respective tubing lines **19**, **20**. Note, such pumps **146**, **148** may also provide greater assistance with a few of the other Fig. 1B alternatives described above. For example, they may provide an advantage in using either of the branch connections **121**, **123** to divert separated component flow back to the donor **11**. A positive force may be desirable and/or even necessary (*e.g.* when device **10** is disposed lower than donor **11**) to move fluids back to the donor **11**. Thus, optional pumps **146**, **148** may provide a desirable assist to any centrifugal (or vortex) pumping action if used as such, from device **10**; or pumps **146**, **148** may provide the sole driving force for drawing separated fluids from device **10**, moving them through respective tubing lines **19**, **20**, then through connections **121**, **123** and then into and through lines **120**, **122** back to the donor **11**. Even if an intermediate line **124** and a Y-connector **125** is used, pumps **146**, **148** may still provide the motive force for flow therethrough as well. Still further even, if an intermediate reservoir (not shown but described above) is used here, these pumps might yet move fluids thereinto and therethrough. However, with the use of such a potential intermediate reservoir, a further pump **142** on line **124** would likely be preferred to draw fluids out of the intermediate reservoir and move these back to the donor **11** through line **124**, manifold **115** and extension **18a**.

Turning now to a few slightly more divergent alternative embodiments, reference is first made to the cross-sectional view shown in Fig. 6. The primary distinction this centrifuge unit **14'** has over that shown, for example, in Fig. 2, is that the separation layer **41** in Fig. 6 has

become the intermediate layer of the rotor **40'** here as opposed to being the top layer of the rotor **40** as in Fig. 2. The previous lower, plasma collection layer **47** (from Fig. 2) has now been flip-flopped up and disposed on top of the separation layer **41** in this Fig. 6 embodiment, and the previously intermediate RBC layer **45** is now the bottom layer **45**. Nonetheless, the functionality remains substantially the same in this embodiment as it was in the Fig. 2 embodiment with the single primary exception that the plasma exits upward out of the separation layer **41** as opposed to downward as in the Fig. 2 embodiment. Further, it is foreseeable that the RBC layer **45** could be disposed on top instead of the plasma layer **47**, which could then remain on the bottom, albeit then being adjacent the separation layer **41**. Separated components still flow out of separation layer **41** through respective outlet ports **56**, **58**, and then flow through respective L-shaped channels **57** and **59** to dump into respective circumferential channels **31**, **33** of housing **30**. Exits out of respective outlet structures **38**, **39** are formed also, as before; except that structure **38**, is formed within a distinctive upper circumferential wall **35a**. Only a few further changes should be addressed. First, the magnetically reactive material **50** is now preferably resident within the RBC layer **45**, the new bottom layer in the Fig. 6 embodiment. And, an effective ceiling **80** (as introduced above) is now preferably included over all of the flow channels in the separation layer **41** allowing only an upward exit through the plasma outlet **56**. Though perhaps not necessary in a gravity-driven inlet scenario, the downward, inward portion **37b** of the inlet aperture structure **37** has been lengthened here to provide continuous inlet fluid guidance until the fluid actually reaches the fluid receiving area **42** of the separation layer **41** of rotor **40'**. Note, aperture structure **37** is not shown axially off-set as in the previous preferred examples; however, it could be so off-set or not, as desired.

A similar, yet perhaps more simplified alternative embodiment **14''** is shown in Fig. 7A. Here also, the separation layer **41** of rotor **40''** is intermediate the RBC and plasma layers **45'**, and **47'**. However, the exit passages **57'**, **59'** shown in Fig. 3 (in dashed lines) and in detail in Figs. 4B and 4C have been substantially reduced/removed. In other words, the respective exit ports **56**, **58** still provide for exit flow from the separation layer **41** as in the embodiment of Fig. 6; with plasma exiting up through outlet **56** and RBCs exiting down through outlet **58**. Only in this Fig. 7A embodiment, the respective outlet passageways **57'** and **59'** are no longer L-

shaped and are extremely short by comparison with the passageways **57**, **59** of Fig. 6. Indeed, the Fig. 7A passageway **57'**, **59'** could be considered coincident with and/or extending no further than the outlet ports **56**, **58**, themselves.

Once separated components exit from the respective ports **56**, **58** (and/or passageways **57'**, **59'**), the fluids are outside the rotor **40**, but still in the housing **30**; in particular, the separated plasma exiting up through port **56** (and passageway **57'**) is then disposed in a space between the upper housing wall **36** and the top of the rotor **40''**, this space being designated **31'**. Space **31'** is analogous to the circumferential channel **31** of the Fig. 6 embodiment and is likewise a circumferentially disposed fluid receiving/containing area which then communicates this fluid to the tangentially disposed exit structure **38** for removal of the fluid from the centrifuge **14''**. A similarly disposed fluid receiving/containing space **33'** is established to receive separated fluids exiting port **58** (and passageway **59'**), such as RBCs in the primary embodiment.

Note, the embodiment in Fig. 7A includes a ceiling **80** as introduced above, but also preferably includes a circumferential rib or ledge member **81** to help retain fluids disposed in respective receiving spaces **31'** and **33'**. An extension of the concept behind the ledge **81** of Fig. 7A is shown in more detail in the alternative embodiment shown in Figs. 7B and 7C. In this embodiment the rotor **40'''** has upper and lower circumferential extensions **82** and **84** which extend to greater radial lengths (measured from rotational axis **43**) than the centrifugal separation channel **46**. The primary advantage is in the heightened definition of the interior receiving channels **31''** and **33''** so that, as shown in even more detail in Fig. 7C, a separated fluid (RBCs, here) flows out of an outlet port, such as port **58**, and then flows radially outwardly (due either to the retained centrifugal energy maintained by the fluid, and/or by action of the still rotating rotor **40'''** to impart centrifugal forces on the exiting fluid with which it is still in contact through the rotor undersurface **85**). Then, the fluid is moved, for the most part, into the tangential exit port, here port **39**, *e.g.*; however, not all of the fluid will immediately flow into the exit port. Some of the fluid will migrate through channel **33''** and seep above extension **84** and move within channel **33''** radially inwardly back away from the exit port **39**. The advantage here is in

the extending of the internal receiving channel 33'' by the extension 84 of the rotor 40''' and the consequent ledge adaptation 81' of housing 30''' which accommodates this migratory radial flow. In the circumstances, the rotor 40''' and the extension 84 continue to provide centrifugal forces to the fluid, thus maintaining a positive flow out through exit port 39 as well as
5 establishing a limit on the radial inward creep of the flow above extension 84. This limit may also create a sort of head pressure which also acts to maintain the movement of the fluid radially outwardly to and through the exit port 39.

Also in this alternative arrangement, the pumping action may be referred to as a single-
10 plate Tesla pump which is employed as shown in Figs. 7B and 7C. The RBC's (or plasma) exit the spinning rotor into a space between the rotor 40''' and stator or housing 30''' where only a small gap (~ 0.030 inches) is present. The small gap between the bottom surface 85 of rotor 40''' and the housing 30''' ensures that the fluid continues to spin with the rotor 40'''. The exact flow profile of the fluid depends on the specific relative geometry of the rotor and stator. When the fluid spins, large pressures are generated against the stator. An exit port 38 is
15 positioned so that this pressure causes fluid to flow therethrough.

An alternative rotor separation channel scheme is shown in Figs. 8 and 9. A challenge in
20 implementing the RBC/plasma device described herein involves the rotor weight balance. According to the preferred embodiments, the rotor is spinning when blood enters the system. Thus, a weight balance is preferably maintained whether the rotor is dry or loaded with blood. A first concept that more directly addresses this is shown in Figs. 8 and 9.

First, the single blood separation pathway 46 of the initially described centrifugation
25 configuration embodiments can be divided into tandem, opposing flow pathways 246a and 246b as shown in the separation layer 41' of Figs. 8 and 9. The two flow paths 246a and 246b balance each other regardless of the material filling the flow paths, whether the materials are air, blood, or any other fluid.

To assist in equally dividing the fluid flow between the two flow paths, blood can be added to the system through port **37** away from the center of rotation (see the axis **43** crosshead on Fig. 8). This alternative was also described above. Thus, the fluid will seek the nearest exit port. The two exit ports **244a'** and **244b'** are preferably rotating so during all inflows they will alternate in receiving the inflow from the single entry port **37**.

To further encourage equal flow distribution, a septum **90** can be added to the receiving cup **42**. The septum **90** preferably extends across the cup **42** and effectively divides it in half with each half having a respective exit port **244a'** and **244b'**. Thus, once the fluid enters a particular half of the receiving cup, its exit pathway is guaranteed. Flow then would continue outward through respective radial transport channels **244a''** and **244b''**; then into the respective circumferential channels **246a** and **246b**. Separation of the composite fluid then continuously occurs and flow continues on around the separation layer **41'** simultaneously in the two channels **246a** and **246b** to the respective outlet channels **252a**, **254a** and **252b**, **254b** and from there, as separated fluids, then out of the centrifugal configuration through respective outlet ports **256a**, **258a** and **256b**, **258b**. From here, the separated fluids would be flowed to respective collection/receiving areas or channels (not shown here), which in one embodiment are like those respective channels **31**, **33** of Figs. 2 and 4A, 4B, 4C (with the primary distinction, of course, of having more than one passageway flowing fluids thereinto). The other alternative embodiments of Figs. 6 and 7A, 7B, 7C, among others not shown here, could also be used herewith. More than two tandem channel configurations could also be used to achieve the weight balancing sought here.

An alternative second concept for a wet/dry weight balance involves a plasma-filled, static column **250** that fills substantially simultaneously with the fluid pathway legs **44**, **52**, **54**, as shown in the separation configuration **41''** in Fig. 10. The plasma column **150** has a geometry that counterbalances the whole blood-in leg **44** and plasma-out and RBC-out legs **52** and **54** as they fill. The counterbalance would preferably have a vent hole **252** for air displacement therefrom during initial filling or priming.

The embodiment of Figs. 11 and 12 is directed to a similar weight balance concept. However, in the embodiment of Figs. 11 and 12, less plasma is relegated to a substantially static disposition as within the channel 150 of Fig. 10. Rather, here, a shortened channel 155 is disposed to receive the exit flow of plasma from the separation configuration 41'''. Then, more plasma is allowed to be in relative continually flowing disposition around the configuration 41''' even though the removal of the plasma outflow tube to the substantially opposite side of the rotor may encourage a substantially no or low flow condition at the meeting position of interface 106 with wall 66. A further alternative here is the use of an optional wall 157 to ensure the location of the interface 106 does not run too far radially outwardly. This wall 157 is not shown in the isometric view of Fig. 12 to underscore the optionality hereof.

Note also, Figs. 9 and 12 are shown without exterior walls such as wall 67 in Figs. 3A, 3B and 5, for example. This is shown this way for convenience in demonstrating the internal components of these alternative rotors. An exterior wall such as wall 67 would be preferred in these embodiments as well.

In two further alternative embodiments as depicted in more detail in Figs. 13 and 14, the centrifuge units 14 generally include similar outer housings 30 and corresponding internal rotor assemblages 40. In broad terms, each outer housing 30 includes a bottom wall 32 (the exterior face of which being the flat-bottom surface 15 described above), one or more circumferential walls 34, 35, and a top wall 36. As before, bottom, circumferential, and top walls 32, 34, 35 and 36 are preferably contiguous (after assembly with a rotor 40) and may at least partially be integrally conjoined or formed, although they may each be separately-formed elements which are subsequently joined. In either case, the walls preferably form a fluid-tight arrangement. A fluid inlet aperture 37a is preferably defined in the top wall 36, and two exit apertures 38a, 39a are preferably defined in and through the bottom wall 32 (although these could be disposed in and through a side wall 34 or 35). Respective inlet and outlet structures 37, 38 and 39 as shown are preferably used to define the respective apertures 37a, 38a and 39a, although other forms could be used. The tubing system 16 and respective fluid storage containers 22, 24 for example, may be connected to the housing 30 as shown in Figs. 1A and 1B (and in dashed lines in Figs. 13 and

14) via the connections of tubing lines 18, 19 and 20 with the respective aperture structures 37, 38 and 39; however, in these embodiments, the bags 22, 24 are preferably disposed below the unit 14 to allow for gravity drainage therefrom into the bags 22, 24.

5 The rotor 40 in Figs. 13 and 14, also as above; particularly includes an outlet channel 52 which then connects to an outlet aperture 56 and an outlet channel 54 which similarly connects to an outlet aperture 58. However, Figs. 13 and 14 show an embodiment wherein the plasma outlet 56 leads first vertically downwardly through the rotor 40 and then it extends downwardly from the rotor 40. This thus provides fluid communication from the outlet 56 to the lower interior
10 channel 31 of the housing 30. In this way then, fluid passing through outlet 56 then empties from the rotor 40 into the rotor housing 30 within the lower channel 31 thereof. Lower channel 31 is then also in fluid flow communication with the outlet 38 which thereby allows for fluid flow out of housing channel 31 into and through outlet 38, and from there, into and through tubing line 20 ultimately to fluid container 24 (see Fig. 1A); where however, the container 24 is preferably
15 disposed below the unit 14 so that separated fluid can flow under the force of gravity from chamber 31 to the container 24.

Similarly, as shown in Fig. 13 and 14, the RBC outlet 58 also leads downwardly through the rotor 40 and communicates outwardly to and provides fluid communication from the RBC
20 outlet 58 to an intermediate interior circumferential channel 33 of the housing 30. Fluid then passes through outlet 58 and then empties from the rotor 40 into the intermediate channel 33 within the rotor housing 30. Channel 33 is then also in fluid flow communication with the RBC outlet 39 thus allowing for fluid flow out of channel 33 into and through outlet 39, and from there, into and through tubing line 19 ultimately to fluid container 22 (again, see Fig. 1A).

25 Moreover, as was true above, the fluid reaching the interior channel 33 is preferably drained by the pull of gravity, into a hanging storage bag 22 which here also is preferably disposed below the centrifugal unit 14.

Also note in Figs. 13 and 14, a piece of metallic material 50 is shown disposed within the
30 lower part of rotor 40. At least one such piece of metallic material 50 is preferably disposed

therein to interact with the rotating magnetic field generated by the base **12** to spin the rotor **40** about the rotational axis **43** (see description below) within the substantially stationary housing **30**.

5 In view of the foregoing, various modifications, adaptations and variations of the structure and methodology of the present invention will become apparent to those skilled in the art without departing from the scope or spirit of the present invention. It is intended that the present invention cover all such modifications, adaptations and variations as limited only by the scope of the following claims and their equivalents.

10

Continued